

METAL SHARK® FL

Conveyor installation below or above conveyed material

METAL SHARK® - The new generation in metal detecting technology

Introducing the METAL SHARK® presenting a completely new design in high sensitivity metal Detectors. The METAL SHARK® provides outstanding sensitivity, accuracy, stability and precision product-effect compensation.

The METAL SHARK® features the latest four channel DDS (direct digital synthesizer) and DSP (digital signal processor) technology. These technologies provide outstanding product-effect compensation High processing speed, DDS and DSP makes the METAL SHARK® the leader in digital metal detection.

Digital balance control - levels temperature and humidity influences.

Auto calibration - fast and easy set-up.

Digital frequency & phase control avoid any drifts. Once calibrated keeps the set-up forever. No need for re-calibration.

Digital noise filters eliminate undesirable signals such as vibrations and shocks.

Multi-channel technology for the optimum recognition of all metals; ferrous, non-ferrous and stainless.

Power supply: Wide input 85-265 V AC works great even with unstable and poor Power sources.

Automatic diagnostics - possible functional defects of the device are displayed on a separate output contact.



METAL SHARK® FL

Typically, the FL types are used in fleece, textile and foil production and provide highest performance in detecting magnetic and nonmagnetic metals.

Industrial design

Sensor and control unit housing are made of sturdy Stainless steel, appropriate for use in the food industry. With a maintenance free design and high quality construction, for reliable operation in the most challenging industrial environments



Easy handling

In practical use, settings of metal detectors often need to be checked quickly and reliably during production. Tectronix attached great importance to user-friendliness: The software is self-explanatory: An interface-manager leads the user step by step through the menus that have to be adjusted. E.g. "product teach" is done with one-button-push.


Intuitive operation

The display shows only the information that is really required. Reduction to the essential makes operation clear and transparent.



Performance validation

The display shows only the information that is really required. Reduction to the essential makes operation clear and transparent. According to HACCP the metal detector is a critical control point and therefore, it must be checked regularly. The performance validation automatically prompts the operator to test the performance of the Metal Shark at pre-set intervals.



Type	METAL SHARK® FL
Conveyor installation	below or above conveyed material
Applications:	Plastic/foil production, panel board production, felt/textile/fleece production
Best Sensitivity*	*depending on product effects and proper installation
Sensing width	200 - 1000 mm
Height above sensor	mm 10 20 30 40 50 60 70 80
Ferrous ball Ø mm	0,8 1,0 1,8 2,2 2,5 3,8 5,0 6,0
Sensing width	1000 - 4000 mm
Height above sensor	mm 10 20 30 40 50 60 70 80
Ferrous ball Ø mm	1,0 1,5 2,2 3,0 3,4 5,5 7,0 8,0
Non-Ferrous	1,2x Ferrous ball Ø
Stainless	1,5x Ferrous ball Ø
Installation	typical horizontal, but each angle is applicable
Metal free zone before/after detector	Fix metal = 250 mm Moving Metal = 500 mm

Power supply	85-264 V / 50-60 Hz
Power input	100 Watts
Ambient temperature	-10...+50 C/ 15...120 F
Product temperature	-20...+80 C
Degree of protection	Control unit IP65 (Nema 4x, 12) Sensor IP67 (Nema 6P, 12)
Sensor head	Stainless steel housing
Control unit	Stainless housing prepared for wall mounting with link cable
Link cable	2,5 m (8,2 feet) with cable protection tube, applies only with wall mounting option for the control unit
Conveyor speed	25 - 3000 mm/sek. (1"-6,6 feet/sec.)
Product effect compensation	Automatically, with teach mode

Tectronix Systems Inc.
 9 – 18812 96th Ave
 Surrey BC V4N 3R1
 Phone 604 607-6028
 FAX 604 607-6026
www.metal-shark.com sales@metal-shark.com

